

iGen**2200**

Digital Inverter Generator

Westinghouse digital inverter generators offer you the ultimate in portable power convenience. Lightweight, fuel efficient and quiet, their mains-quality electrical output can safely power all of your sensitive electronic equipment. They're an essential part of your gear for caravanning and camping and also great for home as a backup power supply.

Features and Benefits

Powerful

High maximum power output of 2,200 Watts is able to run more of your electrical devices.

Lightweight

At only 21 kg it can be easily carried by one person using the ergonomic non-slip handle.

Quiet

Ultra-silent running from only 51 dB(A) that won't disturb you or your neighbours.

Long Running

Up to 19 hours achieved by its fuel-efficient engine and long range 4.3 litre fuel tank.

Easy To Use

Yellow-coloured touch points guide you to the controls required for normal operation.

Mains Quality Electricity

Digital inverter technology safely powers all of your sensitive electronic equipment.

Clean Air Technology

4-stroke OHV petrol engine with Australian and US EPA compliant emission controls.

Plug and Play

Everything you need is in the box. No assembly required. Just add petrol.

Safety Protection

Electrical overload circuit breaker and low engine oil shutdown safeguards.

Warranty Protection

2-year domestic use warranty to safeguard your investment (conditions apply).

1800/2200 STARTING WATTS



Control Panel Functions



Specifications

iGen2200

ENGINE		
Туре	1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled	
Displacement (cc)	79	
Maximum Speed (rpm)	5,300	
Oil Capacity (mL)	350	
Low Oil Shutdown	Yes	
Spark Plug	Torch E6RTC	
Fuel	Unleaded Petrol	
Fuel Tank Capacity (L)	4.3	
Fuel Gauge	No	
Auto-Speed ECO Throttle	Yes	
Starting Method	Recoil	
Hour Meter	Yes	
Run Time @ 450 / 1,800 W	10 / 5 hours	
Noise Level @ 400 / 1,600 W	52 / 61 dB(A) @ 7m	
DIMENSIONS		
Length (mm)	500	
Width (mm)	285	
Height (mm)	450	
WEIGHT		
Weight - Dry (kg)	21	
Weight - Wet (kg)	24.5	

240 VOLT AC ELECTRICAL	
Voltage (V)	240
Frequency (Hz)	50
Number of Phases	1
Continuous Running Power (W) *	1,800
Maximum Starting Power (W)	2,200
Continuous Running Current (A)	7.5
Voltage & Waveform Control	Digital Inverter, Pure Sine Wave Output
Total Harmonic Distortion (THD)	< 2.5%
Receptacle	15 A, IP44
Overload Protection	Electronic
Alternator	Brushless, Permanent Magnet
Output Indicator Light	Yes
5 VOLT DC ELECTRICAL	
Voltage (V)	5
Maximum Current (A)	2.1
Maximum Power (W)	10
Receptacle	USB Type A, IP44

^{*} Rated output at 1.0 power factor.









westinghouseoutdoorpower.com.au